



PRODUCT SAFETY DATA SHEET

Issued: 31/01/06

Revision N°:3

1	IDENTIFICATION OF SUBSTANCE/PREPARATION AND COMPANY		
	1.1 Product:	Flexoid, Sizoid gasket papers	
	1.2 Description:	A gelatine impregnated paper for use as a jointing material within automotive and industrial applications.	
	1.3 Company:	Jointine Products (Lincoln) Ltd, Station Road North Hykeham, Lincoln LN6 9AU Tel: (+44) 01522 690050 Fax: (+44) 01522 690060	
	1.3 Emergency Contact:	Product Safety Manager Tel: (+44) 01522 690050 Fax: (+44) 01522 690060	
2	COMPOSITION/INFORMATION ON INGREDIENTS		
	2.1 Composition:	Approximate composition:	
		Cellulose fibre	55-65%
		Diethylene glycol	15-25%
		Gelatine	5-15%
		Sugars	5-15%
		Formaldehyde	< 0.04%
3	HAZARDS IDENTIFICATION		
	3.1 Health Hazards:	This paper is not a hazard under foreseeable conditions of use. There are no known environmental hazards associated with the product. The product will burn if ignited and then behave in the same way as a conventional paper.	
	3.2 Environment:		
	3.3 Fire Hazards:		
4	FIRST-AID MEASURES		
	In the event of a cut to the skin from the edge of paper, wash with water and cover as for a normal cut or abrasion. If the product is ingested, seek medical attention. Exposure of the eyes to dust may give rise to irritation. Under these circumstances irrigate the eyes with copious amounts of clean water. If any irritation persists, seek medical attention.		
5	FIRE-FIGHTING MEASURES		
	Any conventional extinguishing medium can be used taking into account the location of the fire.		
6	ACCIDENTAL RELEASE MEASURES		



	Not applicable
7	HANDLING AND STORAGE
	Keep the product in a cool place and avoid low humidity. Loss of product moisture will impair performance.

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
	Respiratory and eye protection is recommended if dust is generated during processing of the product. Normal cotton gloves are advised for hand protection.
9	PHYSICAL AND CHEMICAL PROPERTIES
	9.1 Appearance: Flexible gasket paper of dark brown appearance. 9.2 Odour: Slight damp animal odour
10	STABILITY AND REACTIVITY
	This product is stable under normal conditions of storage. Avoid contact with strong acids, alkalis and steam. Auto-ignition temperature is 270-300 °C. Decomposition products are mainly oxides of carbon and water
11	TOXICOLOGICAL INFORMATION
	This product does not represent a risk to health.
12	ECOLOGICAL INFORMATION
	This product is not considered to represent a risk to the environment.
13	DISPOSAL CONSIDERATIONS
	Incineration of the product is the preferred means of disposal. It may also be sent to landfill. Incineration should be carried out with an adequate supply of air to ensure complete combustion. N.B. The user's attention is drawn to the possible existence of regional or national regulations regarding waste disposal.
14	TRANSPORT INFORMATION
	This product is not classified as dangerous according to transport regulations.
15	REGULATORY INFORMATION



JOINTINE PRODUCTS (Lincoln) **LIMITED**

GASKET MATERIALS

Station Road
North Hykeham
Lincoln LN6 9AU

Telephone: 01522 690050
Facsimile: 01522 690060

	This product is not dangerous to health or the environment and is therefore not required to carry any warning labels according to national or EU regulations.
15	OTHER INFORMATION
	Further information on the safety of the product can be obtained from the Product Safety Manager, Jointine Products (Lincoln) Ltd, Station Road North Hykeham, Lincoln LN6 9AU Tel: (+44) 01522 690050 Fax: (+44) 01522 690060

This product safety data sheet is based on the requirements defined in EC Directive 2001/58/EC. However, the product is not classified as dangerous and does not come within the scope of that Directive.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.